

## TECHNICAL DATA SHEET

N. 13FL

Edition 02

www.anticasignoria.it

# CHIC<sup>®</sup> Fine

## DECORATIVE METALLIC EFFECT FINISH

### PRODUCT PROPERTIES

---

CHIC *Fine* is a decorative finish for interiors formulated with acrylic resins in aqueous emulsion with selected pigments and special additives which give the product the following characteristics: GOOD BREATHABILITY, GOOD ADHESION, EASY TO APPLY, GOOD RESISTANCE TO WASHING WITH THE MOST COMMON DETERGENTS.

### USES

---

CHIC *Fine* is suitable for decorating interior walls. It contains pearlescent particles which give a decorative finish with a beautiful visual effect by exploiting the different way light is refracted by them. The visual effect is one which is suitable for both rustic and modern surroundings.

### TECHNICAL CHARACTERISTICS

---

#### SPECIFIC WEIGHT:

1.05 - 1.15 kg/l.

#### VISCOSITY:

3,500 - 4,000 cPs (Brookfield, spindle 5, speed 20 rpm).

#### THEORETICAL COVERAGE PER COAT:

10 - 12 m<sup>2</sup>/l (coverage may vary depending on the roughness, porosity and absorbency of the surface, as well as on the method of application used).

#### DRY RESIDUE:

31% ± 1%.

#### APPEARANCE AND FINISH:

Shiny, smooth, metallic effect finish.

#### VOC EMISSION LIMIT (VOLATILE ORGANIC COMPOUNDS):

EU VOC limit value (Directive 2004/42/EU) for this product (Cat. A/I; BA): 300 g/l (2007); 200 g/l (2010). CHIC *Fine* contains less than 200 g/l of VOC.

### METHOD OF USE

---

#### SURFACE PREPARATION:

On new surfaces fix with one coat of appropriately diluted PRIMER UNIFORMANTE A.S. (masking primer) and after about 3-4 hours apply a coat of the Universal Acrylic Paint, "L'ACRILICO".

On previously painted surfaces, it is recommended that any substances which may prevent adhesion, such as dust, oil and/or grease, and any peeling sections are removed prior to application of the CHIC *Fine* and then proceed as for new surfaces.

#### APPLICATION:

CHIC *Fine* can be applied with pure bristle brush, a pad, a glove, a woollen roller or with a plastic float. The user can customize the final aesthetic appearance by varying the way in which the product is applied. A particularly attractive effect is obtained by applying the product in two successive coats with crossed brush strokes.

#### DILUTION:

The product is ready for use. If necessary, dilute with max 5% by volume of tap water.

#### DRYING TIME at 20°C and 65% RH:

Dust dry after about 2 hours, fully dry after about 24 hours. Fifteen days are required for the product to dry completely and develop resistance to washing.

#### TIME BETWEEN COATS:

About 4 hours at 20°C.

#### ENVIRONMENTAL CONDITIONS:

The product should be applied at environmental and/or surface temperatures of between 5°C and 30°C.

#### CLEANING OF EQUIPMENT:

Clean with water immediately after use.

---

#### PACK SIZES:

2 x 2.5L - 2 x 5L - 6 x 1.25L.

#### AVAILABLE COLOURS:

Silver, Gold.

The bases should be coloured using Toners or the Speedy2 Tinting System.

#### SHELF LIFE AND STORAGE:

Keep the pack tightly closed and store in a cool, dry and frost-free environment.

#### NOTE:

This document has been prepared to the best of our scientific and technical knowledge. The company, Di Donato SpA, does not accept any responsibility for the results obtained with this product as the conditions and methods of application are beyond our control. We therefore recommend that you check the product is suitable for your intended purpose before use.



**Antica Signoria**  
MATERIE DECORATIVE